


# JACKSON/ RAYSICH - PATIO RENOVATION

14420 WISCONSIN AVE ELM  
GROVE WI

## BLU 60 mm

DESCRIPTION: Slab TEXTURE: Slate and HD<sup>2</sup> Slate

### PALLET OVERVIEW



### NOTES

See page 35 to 37 for more technical information. When used in a permeable pavement application, see page 33 and 101 for more technical information.

See page 29 for more information about applications.

\*Sandlewood HD<sup>2</sup> Slate is only available in Eastern States. See page 18 for list of Eastern and Midwestern States.

\*\*HD<sup>2</sup> Slate is only available in USA.

**JOINT WIDTH:** 9/32" (7 mm)  
**% OF SURFACE OPENING:** 3.0 %  
**INFILTRATION RATE:** 570 in./hr  
(14 475 mm/hr)

Specifications per pallet	Imperial	Metric
Cubing	<b>116.82 ft<sup>2</sup></b>	10.96 m <sup>2</sup>
Approx. Weight slate	3 148 lbs	1 428 kg
Approx. Weight slate aged	3 170 lbs	1 438 kg
Approx. Weight HD <sup>2</sup> Slate	3 268 lbs	1 482 kg
Number of rows	11	
Coverage per row	10.62 ft <sup>2</sup>	0.99 m <sup>2</sup>
Linear coverage per row	9.81 lin. ft	3.02 lin. m

	Unit dimensions	in	mm	Units/pallet
	Height	2 3/8	60	44 units
	Width	13	330	
	Length	6 1/2	165	
	Height	2 3/8	60	44 units
	Width	13	330	
	Length	13	330	
	Height	2 3/8	60	22 units
	Width	13	330	
	Length	19 1/2	495	